

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

Please amend the claims as follows:

1. (Currently amended) A method, comprising:  
partitioning a cache array into one or more special-purpose entries and one or more general-purpose entries, wherein special-purpose entries are only allocated for one or more streams having a particular stream ID and the stream ID is stored outside the cache array, wherein the special-purpose entries to use a first cache replacement algorithm and the one or more general-purpose entries to use a second cache replacement algorithm, wherein the first and second cache replacement algorithms are different;

determining if a cross-access scenario exists between at least one of the one or more special purpose entries and at least one of the one or more general purpose entries; and

if the cross-access scenario exists, permitting cross-access of data between the at least one of the one or more special-purpose entries and the at least one of the one or more general-purpose entries that relate to the cross-access scenario.

2. (Original) The method as claimed in claim 1, further comprising allocating the one or more special-purpose entries based on the particular stream ID and a particular input address.
3. (Original) The method as claimed in claim 2, further comprising storing data from the one or more streams in the one or more special-purpose entries when the particular stream ID and the particular input address match a predetermined stream ID and a predetermined input address; and storing data from the one or more streams in the one or more general-purpose entries when the particular stream ID and the particular input address do not match the predetermined stream ID and the predetermined input address.
4. (Previously presented) The method as claimed in claim 3, further comprising determining when the particular stream ID and the particular input address match the predetermined stream ID and the predetermined input address using special-purpose control logic.
5. (Cancelled)

6. (Previously Presented) The method as claimed in claim 4, wherein the one or more streams are special-purpose streams including graphics streams.

7. (Currently amended) A device comprising:

a cache memory array partitioned into one or more special-purpose entries and one or more general-purpose entries, wherein special-purpose entries are only allocated for one or more streams having a particular stream ID, wherein the stream ID is stored outside the cache array;

control logic to determine if a cross-access scenario exists between at least one of the one or more special purpose entries and at least one of the one or more general purpose entries, wherein the control logic comprises:

special-purpose control logic to store data from the one or more streams in the one or more special-purpose entries when the particular stream ID and the particular input address match a predetermined stream ID and a predetermined input address, the special-purpose control logic to implement a first cache replacement algorithm for the one or more special-purpose entries, and

general-purpose control logic to store data from the one or more streams in the one or more general-purpose entries when the particular stream ID and the particular input address do not match the predetermined stream ID and the predetermined input address, the general-purpose control logic to implement a second cache replacement

algorithm for the one or more general-purpose entries, wherein the first and second cache replacement algorithms are different; and

if the cross-access scenario exists, the control logic to permit cross-access of data between the at least one of the one or more special-purpose entries and the at least one of the one or more general-purpose entries that relate to the cross-access scenario.

8. (Previously Presented) The device as claimed in claim 7 further comprising:

the control logic to allocate the one or more special-purpose entries based on the particular stream ID and a particular input address.

9. (Canceled)

10. (Currently amended) The device as claimed in claim 8 [[9]], wherein the special-purpose control logic determines when the particular stream ID and the particular input address match the predetermined stream ID and the predetermined input address.

11. (Original) The device of claim 10, further comprising a DRAM controller integrated with the cache memory array.

12. (Original) The device of claim 11, further comprising an integrated graphics controller, a host AGP controller, and an I/O hub interface coupled to the DRAM controller.

13. (Currently amended) A computer-readable medium having stored thereon a plurality of instructions, the plurality of instructions when executed by a computer, cause the computer to perform the method comprising:

partitioning a cache array into one or more special-purpose entries and one or more general-purpose entries, wherein special-purpose entries are only allocated for one or more streams having a particular stream ID and the stream ID is stored outside the cache array, wherein the special-purpose entries to use a first cache replacement algorithm and the one or more general-purpose entries to use a second cache replacement algorithm, wherein the first and second cache replacement algorithms are different;

determining if a cross-access scenario exists between at least one of the one or more special purpose entries and at least one of the one or more general purpose entries; and

if the cross-access scenario exists, permitting cross-access of data between the at least one of the one or more special-purpose entries and the at least one of the one or more general-purpose entries that relate to the cross-access scenario.

14. (Original) The computer-readable medium of claim 13 having stored thereon additional instructions, the additional instructions when executed by a computer, cause the computer to further perform the method of allocating the one or more special-purpose entries based on the particular stream ID and a particular input address.

15. (Original) The computer-readable medium of claim 14 having stored thereon additional instructions, the additional instructions when executed by a computer, cause the computer to further perform the method of

storing data from the one or more streams in the one or more special-purpose entries when the particular stream ID and the particular input address match a predetermined stream ID and a predetermined input address; and

storing data from the one or more streams in the one or more general-purpose entries when the particular stream ID and the particular input address do not match the predetermined stream ID and the predetermined input address.

16. (Previously presented) The computer-readable medium of claim 15 having stored thereon additional instructions, the additional instructions when executed by a computer, cause the computer to further perform the method of determining when the particular stream ID and the particular input address match the predetermined stream ID and the predetermined input address using special-purpose control logic.

17. (Cancelled)

18. (Previously presented) The computer-readable medium of claim 16, wherein the one or more streams are special-purpose streams including graphics streams.

19. (Currently amended) A system, comprising:

means for partitioning a cache array into one or more special-purpose entries and one or more general-purpose entries, wherein the special-purpose entries are only allocated for one or more streams having a particular stream ID and the stream ID is stored outside the cache array, wherein the special-purpose entries to use a first cache replacement algorithm and the one or more general-purpose entries to use a second cache replacement algorithm, wherein the first and second cache replacement algorithms are different;

means for determining if a cross-access scenario exists between at least one of the one or more special purpose entries and at least one of the one or more general purpose entries; and

if the cross-access scenario exists, means for permitting cross-access of data between the at least one of the one or more special-purpose entries and the at least one of the one or more general-purpose entries that relate to the cross-access scenario.

20. (Original) The system as claimed in claim 19, further comprising  
means for allocating the one or more special-purpose entries based on  
the particular stream ID and a particular stream address.
21. (Original) The system as claimed in claim 20, further comprising  
means for storing data from the one or more streams in the one or more  
special-purpose entries when the particular stream ID and the particular input  
address match a predetermined stream ID and a predetermined input address;  
and  
means for storing data from the one or more streams in the one or more  
general-purpose entries when the particular stream ID and the particular input  
address do not match the predetermined stream ID and the predetermined  
input address.
22. (Previously presented) The system as claimed in claim 21, further  
comprising  
means for determining when the particular stream ID and the particular  
input address match the predetermined stream ID and the predetermined input  
address using special-purpose control logic.
23. (Cancelled)



24. (Previously Presented) The system as claimed in claim 22, wherein the one or more streams are special-purpose streams including graphics streams.

25. (Currently amended) A system, comprising:  
a system memory controller, comprising  
a cache memory array partitioned into one or more special-purpose entries and one or more general-purpose entries, wherein special-purpose entries are only allocated for one or more streams having a particular stream ID and the stream ID is stored outside the cache array, wherein the special-purpose entries to use a first cache replacement algorithm and the one or more general-purpose entries to use a second cache replacement algorithm, wherein the first and second cache replacement algorithms are different;  
control logic, coupled to the cache memory array, the control logic to determine if a cross-access scenario exists between at least one of the one or more special purpose entries and at least one of the one or more general purpose entries;  
if the cross-access scenario exists, the control logic to permit cross-access of data between the at least one of the one or more special-purpose entries and the at least one of the one or more general-purpose entries that relate to the cross-access scenario;  
and system memory connected to the system memory controller.

26. (Previously Presented) The system as claimed in claim 25, further comprising one or more interfaces connected to the system memory controller, including

an I/O hub interface connected to a bus,

a processor interface; and

a host AGP controller connected to the system memory controller via the bus; wherein the cache array receives the cache operation requesting data via the one or more interfaces, and returns a cache hit in response to the cache operation, wherein the cache has a pending fetch for the data in response to a prior cache operation requesting the data.

27. (Previously Presented) The system as claimed in claim 26, wherein the processor interface connects to a processor of a plurality of processors, the plurality of processors including a 16 bit processor and a 64 bit processor.

28. (Previously Presented) The system as claimed in claim 25, wherein the control logic further comprises:

special-purpose control logic to store data from the one or more streams in the one or more special-purpose entries when the particular stream ID and the particular input address match a predetermined stream ID and a predetermined input address; and

general-purpose control logic to store data from the one or more streams in the one or more general-purpose entries when the particular stream ID and the particular input address do not match the predetermined stream ID and the predetermined input address.

29. (Previously presented) The system as claimed in claim 28, wherein the special-purpose control logic determines when the particular stream ID and the particular input address match the predetermined stream ID and the predetermined input address.

30. (Currently amended) A device, comprising:  
a hub interface to use with a 64-bit processing architecture;  
a cache memory array partitioned into one or more special-purpose entries and one or more general-purpose entries; and  
control logic to  
allocate the one or more special-purpose entries based on a particular stream ID and a particular input address, wherein the stream ID is stored outside the cache array, wherein the special-purpose entries to use a first cache replacement algorithm and the one or more general-purpose entries to use a second cache replacement algorithm, wherein the first and second cache replacement algorithms are different;

determine if a cross-access scenario exists between at least one of the one or more special purpose entries and at least one of the one or more general purpose entries;

if the cross-access scenario exists, permit cross-access of data between the at least one of the one or more special-purpose entries and the at least one of the one or more general-purpose entries that relate to the cross-access scenario.

31. (Previously Presented) The device as claimed in claim 30, wherein the control logic further comprises:

special-purpose control logic to store data from the one or more streams in the one or more special-purpose entries when the particular stream ID and the particular input address match a predetermined stream ID and a predetermined input address; and

general-purpose control logic to store data from the one or more streams in the one or more general-purpose entries when the particular stream ID and the particular input address do not match the predetermined stream ID and the predetermined input address.

32. (Previously presented) The device as claimed in claim 31, wherein the special-purpose control logic determines when the particular stream ID and the particular input address match the predetermined stream ID and the predetermined input address.

33. (Previously Presented) The device of claim 32, further comprising a  
DRAM controller integrated with the cache memory array.

34. (Previously Presented) The device of claim 32, further comprising  
an integrated graphics controller, and a host AGP controller.

35-40. (Cancelled)